

VISOKOUČINKOVITA PELET SOBNA PEĆ
HIGH EFFICIENCY PELLET STOVE

ZCY



CENTROMETAL

ZCY MOD. 7 160m³A⁺Daljinski upravljač
RemoteWi-Fi
optionalBOJE
COLORS

Cod. B



Cod. C



Cod. S

TEHNIČKI DETALJI/ TECHNICAL DATA

Mod. 7

Ukupni toplinski učinak (max - min) / Heat input	kW	7,2 - 3,1
Nominalni toplinski učinak (max - min) / Nominal heat output	kW	6,4 - 2,9
Potrošnja peleta (max - min) / Pellet consumption	kg - h	1,45 - 0,6
Iskoristivost (max - min) / Efficiency	%	94,4 - 89,5
Promjer dimovodne cijevi / Smoke outlet tube	ø mm	80
Kapacitet spremnika / Tank capacity	lt - kg	20 - 13
Autonomija (max - min) / Autonomy	h	22 - 9
Potršnja struje na nazivnom učinku / Nominal power input	W	63 - 300
Dimenzije (ŠxDxV) / Dimensions (W x D x H)	mm	440 x 450 x 870
Težina / Net weight	kg	73

15a B-VG

TÜVRheinland®
Precisely Right

EN-14785

CENTROMETAL

ZCY MOD. 10/10C 230m³



Kanalna 10C
Ducted 10C



Daljinski upravljač
model 10



Daljinski upravljač
model 10C



Wi-Fi
ready



Display LCD

BOJE
COLORS



Cod. B



Cod. C



Cod. S

TEHNIČKI DETALJI / TECHNICAL DATA

			Mod. 10	Mod. 10C
Ukupni toplinski učinak (max - min) / Heat input	kW kW		10,1 - 2,84	10,1 - 2,84
Nazivni toplinski učinak (max - min) / Nominal heat output	kW kW		9,05 - 2,64	9,05 - 2,64
Potrošnja peleta (max - min) / Pellet consumption	kg - h kg - h		2,06 - 0,58	2,06 - 0,58
Iskoristivost (max - min) / Efficiency	% %		92,7 - 89,53	92,7 - 89,53
Promjer dimovodne cijevi / Smoke outlet tube	ø mm ø mm		80	80
Kapacitet spremnika / Tank capacity	lt - kg lt - kg		20 - 13	20 - 13
Autonomija (max - min) / Autonomy	h h		22 - 6	22 - 6
Potrošnja struje pri nazivnom učinku / Nominal power input	W W		73 - 300	73 - 300
Dimenzije (ŠxDxV) / Dimensions (W x D x H)	mm mm		440 x 450 x 960	440 x 450 x 960
Težina / Net weight	kg kg		79	81

CENTROMETAL
ZCY MOD. 12/12C
 300m³

A⁺

Kanalna 12C
 Ducted 12C



Daljinski upravljač
 Remote



Radijalni ventilator
 Radial Fan



Wi-Fi
 ready



Displej LCD
 LCD Display



BOJE
 COLORS



Cod. B



Cod. C



Cod. S

TEHNIČKI DETALJI / TECHNICAL DATA

			Mod. 12	Mod. 12C
Ukupni toplinski učinak (max - min) / Heat input	kW	kW	12,3 - 5,2	12,3 - 5,2
Nazivni toplinski učinak (max - min) / Nominal heat output	kW	kW	11,1 - 4,8	11,1 - 4,8
Potrošnja peleta (max - min) / Pellet consumption	kg - h	kg - h	2,5 - 0,6	2,5 - 0,6
Iskoristivost (max - min) / Efficiency	%	%	93,50 - 90,20	93,50 - 90,20
Promjer dimovodne cijevi / Smoke outlet tube	ø mm	ø mm	80	80
Kapacitet spremnika / Tank capacity	lt - kg	lt - kg	25 - 16	25 - 16
Autonomija (max - min) / Autonomy	h	h	26,5 - 6,5	26,5 - 6,5
Potrošnja struje pri nazivnom učinku / Nominal power input	W	W	290 - 300	290 - 300
Dimenzije (ŠxDxV) / Dimensions (W x D x H)	mm	mm	470 x 480 x 1015	470 x 480 x 1015
Težina / Net weight	kg	kg	97	100

15a B-VG



TÜVRheinland®
 Precisely Right

EN-14785

CENTROMETAL
ZCY MOD. 14/14C
 330/350m³



3 ventilatora kod 14C
 3 independent fans 14C



Radijalni ventilator
 Radial Fan



Keramički upaljač
 Ceramic resistance



Daljinski upravljač
 Remote



Kanalna 14C
 Ducted 14C



Wi-Fi
 ready



Displej LCD
 LCD Display



BOJE
 COLORS



Cod. B



Cod. C



Cod. S

TEHNIČKI DETALJI / TECHNICAL DATA

			Mod. 14	Mod. 14C
Ukupni toplinski učinak (max - min) / Heat input	kW kW		13,2 - 3,8	13,2 - 3,8
Nazivni toplinski učinak (max - min) / Nominal heat output	kW kW		12,5 - 3,7	12,5 - 3,7
Potrošnja peleta (max - min) / Pellet consumption	kg - hkg - h		2,7 - 0,8	2,7 - 0,8
Iskoristivost (max - min) / Efficiency	% %		98,00 - 94,76	98,00 - 94,76
Promjer dimovodne cijevi / Smoke outlet tube	ø mmø mm		80	80
Kapacitet spremnika / Tank capacity	lt - kglt - kg		36 - 23	36 - 23
Autonomija (max - min) / Autonomy	h h		29 - 8	29 - 8
Potrošnja struje pri nazivnom učinku / Nominal power input	W W		189 - 300	189 - 300
Dimenzije (ŠxDxV) / Dimensions (W x D x H)	mm mm		495 x 530 x 1020	495 x 530 x 1020
Težina / Net weight	kg kg		144	149

CENTROMETAL

ZCY MOD. 16/16C

380/400m³



3 ventilatora kod 16 C
3 independent fans 16C



Radijalni ventilator
Radial Fan



Keramički grijač
Ceramic resistance



Daljinski upravljač
Remote



Kanalna 16C
Ducted 16C



Wi-Fi
ready



Displej LCD
LCD Display



BOJE
COLORS



Cod. B



Cod. C



Cod. S

TEHNIČKI DETALJI / TECHNICAL DATA

			Mod. 16	Mod. 16C
Ukupni toplinski učinak (max - min) / Heat input	kW kW		16,3 - 3,8	16,3 - 3,8
Nazivni toplinski učinak (max - min) / Nominal heat output	kW kW		15,2 - 3,7	15,2 - 3,7
Potrošnja peleta (max - min) / Pellet consumption	kg - kg - h		3,34 - 0,8	3,34 - 0,8
Iskoristivost (max - min) / Efficiency	% %		98,00 - 93,48	98,00 - 93,48
Promjer dimovodne cijevi / Smoke outlet tube	ø mmø mm		80	80
Kapacitet spremnika / Tank capacity	lt - kg - kg		36 - 23	36 - 23
Autonomija (max - min) / Autonomy	h h		29 - 7	29 - 7
Potrošnja struje pri nazivnom učinku / Nominal power input	W W		192 - 300	192 - 300
Dimenzije (ŠxDxV) / Dimensions (W x D x H)	mm mm		495 x 530 x 1080	495 x 530 x 1080
Težina / Net weight	kg kg		151	153

15a B-VG



TÜVRheinland®
Precisely Right

EN-14785